



50kW HYBRID INVERTER / 72 / 86 / 100kWh BATTERY

Air Cooling Commercial & Industrial Energy Storage System

Flexible

Highly integrated
All pre-assembled
Extendable

Reliable


DC electric circuit safety protection
Multi level battery protection
Fire suppression system

Efficient

Intelligent cooling system
< 10ms Switching Off /
On-grid


Smart

Intelligent cloud platform
management, real-time
monitoring of operational status



50kW HYBRID INVERTER / 72 / 86 / 100kWh BATTERY

Air Cooling Commercial & Industrial Energy Storage System



	Model	SSES72-50K		SSES86-50K	SSES100-50K
Battery	Battery Type	LiFePO4			
	Nominal Capacity	280Ah			
	Battery Configuration	1P80S	1P96S	1P112S	
	Nominal Energy	71.68kWh	86.016kWh	100.352kWh	
	Nominal Voltage	256V	307.2V	358.4V	
	Operating Voltage Range	224~288V	268.8~345.6V	313.6~403.2V	
	Max.Continuous Charge / Discharge Current	140A			
	Max. Charge-discharge Efficiency	95%(@25°C~30°C, 0.5P)			
	Charge / Discharge Rate	0.5P			
	Cycle Life	≥ 6000 (@25°C ± 2°C , 0.5P / 0.5P, 70% EOL)			
PV	Max.DC Input Voltage	1000V			
	MPPT Voltage Range	200~950V			
	DC Inputs	2 / 2 / 2 / 2			
	Max.Input Current	40A*4			
Back-up	Rated Output Power	50kW			
	On / Off-grid Switching Time	<10ms			
	Peak Output Apparent Power	1.5 Times Of Rated Output Power, 10s			
System	Max. AC Output Power	55kW			
	Grid Type	3L / N / PE			
	AC Output Frequency	50 / 60HZ			
	AC Output Voltage	400±5%V			
	Voltage Harmonic Distorion	<3% @Linear Load			
	AC Max. Output Current	83A			
	Power Factor	0.8 Leading ... 0.8 Lagging			
	Ingress Protection	IP54			
	Protective Class	Class I			
	Anti-Corrosion Grade	C4			
	Max. System Efficiency	88%			
	Charge Operating Temperature	0°C ~45°C			
	Discharge Operating Temperature	-20°C ~50°C			
	Operating Temperature Range	-20°C ~50°C			
	Relative Humidity	5~95 % (non-condensing)			
	Max. Working Altitude	3000(>2000m derating)			
	Communication	CAN / RS485 / WiFi / LAN (Optional)			
	Cooling	Air Cooling			
	Dimension	1150 × (1325±5) × 2280 mm			
	Net Weight	≤1140kg	≤1240kg	≤1340kg	
	Max. Parallel	5			

